



A portable variant of Atlas, for harsh environments.

The instrument is equipped with high-resolution delta-sigma 32bit ADCs, all the channels are synchronized and the sample rate is adjustable up to 1000 sps per channel.

The internal memory (up to 1TB) has two independent recording zones: the ring-buffer which is dedicated to continuous sampling, and the triggering which is used for event sampling. The data format is MiniSEED.

The built-in GNSS receiver synchronizes the system clock with the absolute time so that a network of several units can be created where all the channels are synchronized. Using the trigger criteria that is available in the firmware, it is possible to distinguish environmental vibrations from seismic events.

ATLAS-C

LIGHT AND PORTABLE DIGITAL RECORDER

KEY FEATURES

ADC RESOLUTION 32 bit

DYNAMIC RANGE > 136dB@100 sps

SAMPLING RATE 25, 50, 100, 200, 250,
500, 1000 sps

SYNCHRONOUS SAMPLING

LAN, WIFI

INTEGRATED 4G MODEM (OPTIONAL)

BUILT-IN GNSS RECEIVER

INTEGRATED UPS

INPUTS COMPATIBLE WITH ACCELEROMETERS
VELOCIMETERS GEOPHONES MICROBAROMETERS

MINISEED DATA FORMAT

COMPATIBLE WITH EARTHWORM, GEOPSY,
SEISGRAM2K

* 3 active channels



Seismological networks Structural monitoring and surveys Post-seismic damage analysis	APPLICATIONS	FILE TRANSFER Via Ethernet 10/100, WiFi (optional) or integrated 4G modem (optional) WIFI MODE SOFT AP function METADATA RESP file available on IRIS DATA DOWNLOAD Through SCP protocol based program or via web interface VPN Compatible with OpenVPN and IPSec	COMMUNICATION
INPUT CHANNELS 3, 6 or 9 differential SAMPLING Simultaneous INPUT IMPEDANCE 90KΩ or opt 2MΩ INPUT VOLTAGE 40, 20, 10, 5, 2.5, 1.25, 0.625 Vpp SENSOR COMPATIBILITY Accelerometers (FBA, MEMS), Geophones, Seismometers and Microbarometers	INPUTS	FORMAT Seedlink protocol management for real-time interface with most common seismic programs such as SeisComP3 and Earthworm STREAM Seismic and State-of-Health ALARMS Management towards remote monitoring server	DATA STREAMING
ADC Sigma-delta 32 bit synchronous sampling DYNAMIC RANGE > 136dB @ 100 sps SAMPLE RATES 25, 50, 100, 250, 500, 1000* sps * (3 ch active) ADVANCED FEATURES Dual Sampling ANTI-ALIASING FILTER FIR linear or minimum phase ADDITIONAL DIGITAL FILTERS Low-pass and High-pass filter	A/D CONVERSION	INTERFACE Web Server CONTROL Connection and management on remote servers UPDATES Remote software update (local network or via internet) ADVANCED FEATURES Multiple units can be connected to the network (Ethernet, WiFi or 4G) acting as a single multi-channel instrument	CONFIGURATION
TRIGGERS STA/LTA and threshold independent for each channel AND/OR configuration on all channels Trigger broadcasting towards recorders in the network	TRIGGERS	POWER SUPPLY 9 ÷ 28 Vdc - AC/DC adapter included POWER CONSUMPTION < 2 W SENSOR POWER Provided from sensor connector UPS Back-up LiPO battery, autonomy > 24 hours ALARMS Remote alarms management in case of blackout ACCESSORIES External battery pack and solar panel options	POWER SUPPLY
FORMAT MiniSEED INTERNAL MEMORY 32GB standard, optionally up to 1TB RING BUFFER DATA RECORDING (16 or 32 days, depending on mem. size) plus strong motion events ADV. FEAT. Periodic generation of ambient noise and post-seismic analysis	STORAGE	STORAGE TEMPERATURE RANGE - 40 ÷ +85°C HUMIDITY 0 to 100% OPERATING TEMPERATURE RANGE Without battery - 40 ÷ +85°C * *LiPo batteries can be charged in the range 0 ÷ +45°C while discharge is allowed in the range of -20 ÷ +70°C. If the temperature is out of range, the LiPo battery will be inhibited by the electronics	OP. CONDITIONS
TIMING SOURCE GNSS or NTP - Absolute Time UTC through high sensitive integrated GNSS receiver ACCURACY in GNSS signal loss condition: ± 1 ppm (32 s/year) Accuracy with GNSS signal < 1 μS	SYNCHRONIZATION	CASE Plastic PROTECTION GRADE IP67 DIMENSIONS 270 x 230 x 120 mm WEIGHT ≈3 Kg	PHYSICAL
LEDs Heartbeat, 4G, WiFi, GNSS, Ethernet, Power BUTTONS Power on/off and WiFi enable/disable on the same button	UI		

