



VLS9000

Velocity Limiting System For PT9000

Prevents damage from cable free release.

Provides safer operation.

Our Velocity Limiting System (VLS) is an option available for our PT9101, PT9150, PT9420, PT9510 and PT9600 cable extension transducers that prevents the measuring cable from ever reaching a damaging velocity during an accidental free release.

This option is ideal for applications that require frequent cable disconnection and reconnection. It prevents expensive unscheduled downtime due to accidental cable mishandling or attachment failure. The guides below define the PT9000 datasheets which support VLS as a Standard Option with quick delivery. Please contact us for availability of datasheets or options not shown.

Velocity Limiting System Performance Specification

Data Sheets	Measuring Cable Tension Option	Max Retraction Velocity
PT9101, PT9150, PT9420, PT9510, PT9600	1 and 3	40 - 55 inches/sec
	2 and 4	40 - 80 inches/sec
PT9101 Ext Range PT9150 Ext Range PT9420 Ext Range PT9510 Ext Range PT9600 Ext Range	n/a	40 - 55 inches/sec

How to Order

Find the appropriate PT9000 model shown below on the left and use the corresponding guide to the right to configure the VLS model number. Available options for each model are shown in grey. Consult appropriate PT9000 datasheet for complete description and details of options.

How to Order

PT9101



75 to 550-inch Ranges					
VLS9101 -	0	1	2	3	4
0075	1	1	1	1	1
0100	2	2	2	2	2
0150	3	3	3	3	3
0200	4	4	4	4	4
0250				5	5
0300				6	6
0350					7
0400					
0450					
0500					
0550					

600 to 1700-inch Ranges					
VLS9101 -	0	1	2	3	4
0600	1	1	1	1	1
0800	3	2	2	2	2
1000			3	3	3
1200			4	4	4
1500				5	5
1700				6	6
					7

PT9420



75 to 550-inch Ranges					
VLS9420 -	0	1	2	3	4
0075	1	1	1	1	1
0100	2	2	2	2	2
0150	3	3	3	3	3
0200	4	4	4	4	4
0250				5	5
0300				6	6
0350					7
0400					
0450					
0500					
0550					

600 to 1700-inch Ranges					
VLS9420 -	0	1	2	3	4
0600	1	1	1	1	1
0800	3	2	2	2	2
1000			3	3	3
1200			4	4	4
1500				5	5
1700				6	6
					7

PT9510



75 to 550-inch Ranges					
VLS9510 -	0	1	2	3	4
0075	1	1	1	1	1
0100	2	2	2	2	2
0150	3	3	3	3	3
0200	4	4	4	4	4
0250				5	5
0300				6	6
0350				7	7
0400				8	
0450					
0500					
0550					

600 to 1700-inch Ranges					
VLS9510 -	0	1	2	3	4
0600	1	1	1	1	1
0800	3	2	2	2	2
1000			3	3	3
1200			4	4	4
1500				5	5
1700				6	6
				7	7
				8	

VLS9000

Velocity Limiting System For PT9000

PT9600



75 to 550-inch Ranges

VLS9600-	R	A	B	C	D
0075	1	1	1	F01	
0100	2	2	2	F02	
0150	3	3	3	S01	
0200	4	4	4	S02	
0250				S04	
0300					
0350					
0400					
0450					
0500					
0550					

600 to 1700-inch Ranges

VLS9600-	R	A	B	C	D
0600	1	1	1	F01	
0800	3	2	2	F02	
1000			3	S01	
1200			4	S02	
1500				S04	
1700					



LUNITEK

LUNITEK srl
via Variante Aurelia 115 Bis
19038 SARZANA (SP) ITALY
CF/P.IVA 01107260117

tel. +39 0187 692070
fax +39 0187 622339
www.lunitek.it
info.sarzana@lunitek.it



Azienda con sistema di gestione
certificato Nr. 5010011753
secondo la norma UNI EN ISO 9001